## Over-Door Light



Indigo Care has designed a simple, effective, yet non-obstructive nurse call Over- Door light. The standard mounting plate provides three LED colours in one package-Red, Green and Yellow. Using current LED technology, the light is intensely bright but consume only low power. The output from the source (room controller) can be reconfigured to drive a single LED or all of the LED's at one time. The display is either in clear or frost acrylic. Trigger output to either low or high is by selectable jumper link. Wiring installation is either by RJ45 or 4-way terminal block.

Product Specification Sheet is provided upon request.

## **Part Number:**

MED-ODL-V(x)AH- for Active High, Clear Acrylic MED-ODL-V(x)AL- for Active Low, Clear Acrylic MED-ODL(F)-V(x)AH- for Active High, Frost Acrylic MED-ODL(F)-V(x)AL- for Active Low, Frost Acrylic

## **Key Specifications:**

- Clean & Smart Looking ODL
- Non-Obtrusive Design
- Bright & Easy to See
- High Refractive Prism Clear or Frost
- 3 LED colour: Red, Green, Yellow
- Extra Long Life LED
- Low Power Consumption-Robust LED
- Dimensions:
- 118 mm (L) x 76 mm (W) x 13 mm (D)
- Input Supply: +12-27VDC
- Dimension-equivalent top Clipsal 4000
- Broad Viewing Angle: 120 degrees
- Operating temperature:
- -40 to 100 deg Celsius
- Wiring: RJ45 & Terminal Block
- Trigger Output: Selectable Low or High
- Optional: Buzzer

Easy to Use

**Cost Effective** 

Integrates to most Nurse Call Systems



HORIZON ELECTRONIC COMPONENTS Pty Ltd 2/71 Rushdale Street, Knoxfield, VIC, 3180 PH +61 3 9763-2988 FAX +61 3 9763-3811 www.indigocare.com.au ABN 36007302801

**ORDER INFORMATION** 

Fax or email your purchase orders to 03-9763-3811

Or email sales@indigocare.com.au